ENGINEERS / SCIENTISTS / PROGRAM MANAGERS



September 26, 2014

CAPT Jeff Church, REHS, CSP, CIH
Senior Program Manager, Environmental,
Health, and Safety Services
Federal Occupational Health (FOH)
Program Support Center
U.S. Department of Health and Human Services
4550 Montgomery Avenue, Suite 950
Bethesda, MD 20814

via e-mail: Jeffrey.Church@foh.hhs.gov

Re: Indoor Air Quality (IAQ) Assessment Services Report

Environmental Protection Agency (EPA) Potomac Yard (North) Building – 5th Floor

2733 Crystal Drive, Arlington, VA 22202

Tidewater Project No.: 5379-005

Dear CAPT Church:

On August 27, 2014, Tidewater, Inc. (Tidewater), represented by Industrial Hygienist, Mr. Jason M. Gauthier, performed an Indoor Air Quality (IAQ) assessment survey in select areas of the 5th Floor of the EPA Potomac Yard (North) building located at 2733 Crystal Drive in Arlington, Virginia. This assessment was conducted at the request of Federal Occupational Health (FOH) in response to IAQ complaints made by multiple tenant employees working on the 5th Floor of the building. These complaints included adverse health effects the employees attributed to the recent release of "Garden Safe Houseplant & Garden Insect Killer", a household pesticide containing Pyrethrum and Piperonyl Butoxide, within Office 5722. The pesticide was reportedly released within Office 5722 on July 3, 2014.

At the request of FOH, Tidewater performed an IAQ assessment on the 5th Floor of the building to document prevalent IAQ conditions. The Scope of Work (SOW) for the IAQ assessment, as approved by FOH, included the following:

- The collection of temperature, relative humidity, carbon dioxide (CO₂), and carbon monoxide (CO) measurements using a direct read instrument in the incident office (Office 5722) and surrounding areas;
- The collection of Total Volatile Organic Compounds (TVOCs) measurements using a direct read instrument in the incident office (Office 5722) and surrounding areas;
- The collection of nine (9) air samples for laboratory analysis for Pyrethrins and Piperonyl Butoxide in the incident office (Office 5722), surrounding complaint areas, and noncomplaint areas to establish typical background levels for these compounds; and
- The collection of nine (9) wipe samples for laboratory analysis for Pyrethrins and Piperonyl Butoxide residues from high contact surfaces in the incident office (Office 5722), surrounding complaint areas, and non-complaint areas to establish typical background residue levels for these compounds.



Tidewater was authorized to conduct this IAQ assessment via the acceptance of TI2E's proposed SOW and cost estimate, dated August 26, 2014, by CAPT Church. Tidewater was verbally authorized by Mr. Daniel Fielden, Contractor Industrial Hygienist for the USEPA/OARM/OA/SHEMD, to conduct this assessment on August 27, 2014. Tidewaters' industrial hygienist was accompanied by Mr. Fielden throughout the duration of this assessment.

Visual Observations

Tidewater's investigation included a visual inspection of the incident office (Office 5722), surrounding complaint areas (Suite 5720, Office 5741, Conference Room 5771, Suite 5780, and Office 5782), and non-complaint areas (Pantry 5500, Pantry 5400, and Conference Room 4840) for indications of general indoor air quality problems. The results of Tidewater's observations are as follows:

- Building materials observed on the affected areas generally consisted of gypsum wallboard walls, suspended ceiling tile grid systems, and carpeted floors. Gypsum board ceilings were also observed in a few discreet locations. The perimeter walls contained large windows. The floors were generally accessed via a central elevator lobby.
- The tenant occupied spaces were generally observed to include open work stations/cubicle work areas, offices, conference rooms, and centrally located pantries/break areas and service center areas (printers, copies, etc.) Building mechanical spaces and restroom facilities were located in the central core area.
- Ceiling-mounted air exchange registers located throughout the tenant spaces were observed to be generally clean with only minor accumulations of dust.
- Tidewater observed the tenant occupied spaces to be generally clean and well maintained. No industrial chemicals or waste storage areas were observed within the tenant spaces.
- Tidewater did not observe any evidence of suspect microbial growth, active water intrusion, or standing water within the tenant spaces.
- Tidewater did not detect any unusual odors emanating from any of the areas assessed during this survey.

Air Quality Measurements

During the assessment, Tidewater recorded temperature, relative humidity, carbon dioxide (CO₂), and carbon monoxide (CO) measurements within the incident office, surrounding complaint areas, and non-complaint areas using a MetroSonics aq-5000 IAQ monitor (Serial Number 2157, Factory Calibrated May 9, 2014.) Measurements of TVOCs were also recorded within these areas using a MiniRAE 2000 direct read Photo Ionization Detector (PID) (Serial Number 110-002160, Factory Calibrated July 29, 2014.)

Measurements were recorded after allowing the devices to become acclimated to the ambient temperature and relative humidity for five (5) minutes. Background/ambient readings were obtained from the exterior of the building (4th Floor Patio/Green Roof area) for comparative analysis. Readings were recorded between approximately 1400 PM and 1429 PM.



The recorded IAQ readings are summarized in Table 1 below.

TABLE 1: IAQ Assessments Air Testing Results EPA Potomac Yard (North) – 5th Floor August 27, 2014

Location	Temperature (°F)	Relative Humidity (%)	Carbon Monoxide (ppm)	Carbon Dioxide (ppm)	Total VOCs (ppm)
Office 5722 (Incident Office)	71.7	55.3	0.0	640	0.5
Suite 5720 (Impacted Suite)	72.2	54.9	0.0	716	0.3
Office 5741 (Impacted Individual)	72.5	54.1	0.0	656	0.0
Conference Room 5771 (Impacted Individuals)	72.1	53.0	0.0	669	0.0
Suite 5780 (Impacted Suite)	70.6	53.2	0.0	668	0.0
Office 5782 (Impacted Individuals)	71.5	53.7	0.0	637	0.0
Pantry 5500 (Non-complaint Area, same HVAC zone as Incident Office)	71.6	55.4	0.0	750	0.0
Pantry 5400 (Non-complaint Area, different HVAC zone than Incident Office)	71.9	55.3	0.0	729	0.0
Conference Room 4840 (Un-impacted Area)	72.0	50.0	0.0	813	0.0
4 th Floor Patio/Green Roof (Outside/Ambient)	83.5	51.7	0.0	545	0.0



Temperature

According to the American Society for Heating, Refrigeration, and Air Conditioning Engineers (ASHRAE) guidelines Standard 55 – 2010, the temperature range in summer/ transitional season should be maintained between 73°F and 79°F for maximum occupant comfort. The ASHRAE guideline for temperature for winter/ transitional season is between 68.0°F and 74.5°F.

Temperature readings recorded in the assessed areas ranged from 70.6°F to 72.5°F, compared with an outside temperature of 83.5°F. All of the interior readings were marginally below the ASHRAE recommended comfort range for the summer/transitional season. Tidewater does not believe the temperature readings being recorded marginally below the ASHRAE recommended comfort range to be an indication of adverse IAQ within the building, or to be a contributing factor to the incident complaints.

Relative Humidity

Per ASHRAE Standard 62.1 – 2010, a maximum recommended relative humidity level of 65% is recommended to reduce the likelihood of condensation on cold surfaces and potential microbial growth. The ideal comfortable relative humidity range has been reported as 40% to 60%, as long as building materials or contents are not adversely affected. OSHA recommends humidity control within a 20% to 60% range in their technical manual for indoor air quality investigations.

Measurements of relative humidity recorded in the assessed areas ranged from 50.0% to 55.4%, compared with 51.7% outside the building. All of the interior readings were within the ASHRAE and OSHA recommended ranges.

Carbon Dioxide

ASHRAE Standard 62.1 - 2010 recommends that indoor CO_2 levels not exceed 700 parts per million (ppm) of CO_2 in excess of the outside air concentration. At a differential higher than 700 ppm, 80% of un-adapted individuals (visitors) would find air quality unacceptable (based upon non-specific contaminants, such as body odor and other bio-effluents.) This level should be used as a guideline that helps maximize comfort for all occupants.

Carbon dioxide readings recorded in the assessed areas ranged from 637 ppm to 813 ppm, compared with an outside reading of 545 ppm. All of the interior carbon dioxide readings were within the ASHRAE recommended guideline.

Carbon Monoxide

The OSHA permissible exposure limit for CO is 50 ppm for an eight-hour permissible exposure limit. OSHA has proposed a time-weighted average exposure limit of 35 ppm, a ceiling level of 200 ppm, and an Immediately Dangerous to Life and Health (IDLH) level of 1,200 ppm. The Indoor Air Quality Association guideline for CO in an occupied indoor environment is 9 ppm.

All recorded CO concentrations collected during this assessment were 0.0 ppm. These measurements indicate that CO concentrations within the building are within acceptable limits.



Total Volatile Organic Compounds

Although no recommended guidelines for airborne concentrations of total VOC's currently exist, guidelines for individual constituents do exist. The American Conference of Governmental Industrial Hygienists (ACGIH) has established a Threshold Limit Value (TLV) for total diesel hydrocarbons of 15 ppm for diesel vapor exposure, measured as an 8-hour time-weighted average (TWA).

Recorded TVOC concentrations collected during this assessment ranged from 0.0 ppm to 0.5 ppm. These measurements indicate that TVOC concentrations within the building are within acceptable limits.

Pyrethrins and Piperonyl Butoxide Air Sampling

Tidewater collected a total of nine (9) air samples from representative building areas for laboratory analysis for Pyrethrins and Piperonyl Butoxide during this assessment. One (1) field blank sample was also submitted to the laboratory for Quality Assurance/ Quality Control (QA/QC) purposes. The samples were collected between approximately 1226 PM and 1502 PM. The sample locations and corresponding sample identifications are delineated below:

- Sample 082714-A01 Office 5722 (Incident Office);
- Sample 082714-A02 Suite 5720 (Impacted Suite);
- Sample 082714-A03 Office 5741 (Impacted Individual);
- Sample 082714-A04 Conference Room 5771 (Impacted Individuals);
- Sample 082714-A05 Suite 5780 (Impacted Suite);
- Sample 082714-A06 Office 5782 (Impacted Individuals);
- Sample 082714-A07 Pantry 5500 (Non-complaint Area, same HVAC zone as Incident Office);
- Sample 082714-A08 Pantry 5400 (Non-complaint Area, different HVAC zone than Incident Office);
- Sample 082714-A09 Conference Room 4840 (Un-impacted Area); and
- Sample 082714-A10 Field Blank.

Each sample was collected on a quartz filter (XAD-2 OVS) within a solid sorbent tube (SKC 226-58) using a dedicated Gillian BDXII air collection pump operating at a flow rate of 1.0 liter per minute (L/min.) The samples collected in the assessed areas had run times ranging from 123 minutes to 137 minutes for total volumes ranging from 123 liters to 137 liters of air. The sample media was stored in a transport cooler with an ice pack prior to the sampling event and during shipment to the laboratory. The samples were submitted for analysis to ALS Environmental (ALS), an AIHA-accredited analytical laboratory located in Salt Lake City, Utah, following rigorous chain of custody guidelines. The samples were analyzed for Pyrethrins and Piperonyl Butoxide via Gas Chromatography in accordance with modified NIOSH 5605 methodology.

For evaluation purposes, the sample results were compared to the current OSHA PEL, ACGIH TLV, and/or NIOSH REL (if available.) Established exposure limits for Pyrethrins include a PEL, TLV, and REL of 5 milligrams per cubic meter (mg/m³.) No occupational exposure limits have been established for Piperonyl Butoxide at this time; however, reference to an arbitrary limit of

ENGINEERS / SCIENTISTS / PROGRAM MANAGERS



10 mg/m³ was included on OSHA's sampling and analytical methods webpage for this compound.

Analysis of the air samples collected in the assessed areas indicated concentrations of Piperonyl Butoxide ranging from less than 0.0036 mg/m³ to less than 0.0041 mg/m³. Analysis of the field blank sample indicated a concentration of less than 0.50 micrograms per sample (µg/sample.) All of these results were below the arbitrary exposure limit for this compound, as well as below the laboratory's limit of detection for the analytical method.

A copy of the analytical reports, including Chain of Custody Forms, is included as Attachment A. A site diagram indicating sampling locations is included as Attachment B.

Pyrethrins and Piperonyl Butoxide Residues Wipe Sampling

Tidewater collected a total of nine (9) wipe samples from representative building areas for laboratory analysis for Pyrethrins and Piperonyl Butoxide residues during this assessment. The samples were generally collected from a desk top, conference table, or other horizontal surface with high contact potential in the assessed areas. One (1) field blank sample was also submitted to the laboratory for QA/QC purposes. The sample locations and corresponding sample identifications are delineated below:

- Sample 082714-W01 Office 5722 (Incident Office), Desk;
- Sample 082714-W02 Suite 5720 (Impacted Suite), Desk;
- Sample 082714-W03 Office 5741 (Impacted Individual), Desk;
- Sample 082714-W04 Conference Room 5771, Table (Impacted Individuals);
- Sample 082714-W05 Suite 5780 (Impacted Suite), Desk;
- Sample 082714-W06 Office 5782 (Impacted Individuals), Desk;
- Sample 082714-W07- Pantry 5500, Table (Non-complaint Area, same HVAC zone as Incident Office);
- Sample 082714-W08 Pantry 5400, Counter (Non-complaint Area, different HVAC zone than Incident Office):
- Sample 082714-W09 Conference Room 4840, Table (Un-impacted Area); and
- Sample 082714-W10 Field Blank.

Each sample was collected using a laboratory-provided sterile cotton gauze pad moistened prior to the sample collection with isopropyl alcohol. An approximate two inch by two inch (2" x 2") area was wiped at each sample location for a total sampled area of four square inches (4 in².) The wipe samples were collected after recording the air quality measurements and collecting the air samples at each location.

The sample media was stored in a transport cooler with an ice pack prior to the sampling event and during shipment to the laboratory. The samples were submitted for analysis to ALS Environmental, an AlHA-accredited analytical laboratory located in Salt Lake City, Utah, following rigorous chain of custody guidelines. The samples were analyzed for Pyrethrins and Piperonyl Butoxide via Gas Chromatography in accordance with modified NIOSH 5605 methodology.

Regulatory limits for concentrations of Pyrethrins and Piperonyl Butoxide residues on contact surfaces do not appear to have been established at this time.



Analysis of all wipe samples collected indicated that concentrations of Pyrethrins and Piperonyl Butoxide residues in all samples were less than 0.50 micrograms per sample (µg/sample.) All of these results were below the laboratory's limit of detection for the analytical method, indicating no detectable concentrations of Pyrethrin and Piperonyl Butoxide residues remained on the sampled surfaces.

A copy of the analytical report, including Chain of Custody, is included as Attachment A. A site diagram indicating sampling locations is included as Attachment B.

Conclusions and Recommendations

Based on the results of the visual inspection and the measurements of air quality parameters, Tidewater offers the following conclusions and recommendations:

- Tidewater's observations of the incident office, surrounding complaint areas, and noncomplaint areas during this assessment did not reveal any readily observable indications of general indoor air quality problems.
- Temperature measurements recorded in the assessed areas were all marginally below the ASHRAE recommended comfort range for the summer/transitional season. Tidewater does not believe these temperature readings are an indication of adverse IAQ within the building, or are likely to be a contributing factor to the incident complaints.
- Air quality measurements recorded by Tidewater during the assessment indicated relative humidity, carbon dioxide, carbon monoxide, and TVOC levels within the assessed areas were within regulatory and recommended guidelines.
- Analytical results for the Pyrethrins air samples were all below the established exposure limits, as well as below the laboratory's limit of detection for the analytical method.
- Analytical results for the Piperonyl Butoxide air samples were all below the arbitrary exposure limit for this compound, as well as below the laboratory's limit of detection for the analytical method.
- Analytical results for the Pyrethrins and Piperonyl Butoxide residues wipe samples were all below the laboratory's limit of detection for the analytical method, indicating no detectable concentrations of Pyrethrins and Piperonyl Butoxide residues remained on the sampled surfaces.

Based on these conclusions, Tidewater does recommend that the HVAC system serving the complaint area be adjusted, if feasible, to maintain temperatures within the recommended ASHRAE comfort ranges throughout the year.

Qualifications

Tidewater has endeavored to assess existing conditions in select areas of the 5th Floor of the EPA Potomac Yard (North) building, located at 2733 Crystal Drive in Arlington, Virginia, as they pertain to IAQ complaints related to the release of "Garden Safe Houseplant & Garden Insect Killer", a household pesticide containing Pyrethrum and Piperonyl Butoxide, within Office 5722 on July 3, 2014. Regardless of the thoroughness of our investigation, it is possible that some contributing factor has been overlooked or that circumstances have changed without our knowledge. Our results are based on the observations made on the day of our assessment,



ENGINEERS / SCIENTISTS / PROGRAM MANAGERS

analytical laboratory data representative of the time samples were collected, and information provided by FOH. Actual conditions vary from day to day throughout the year.

Tidewater appreciates the opportunity to provide consulting services for Federal Occupational Health on this matter. Please contact us should any questions arise concerning this report or if we may be of further assistance.

Sincerely,

Tidewater, Inc.

Jason M. Gauthier Project Manager

Jonathan N. Schatz, MS, CES, CEI

Manager, IH Services

Skanda Abeyesekere, MS, CIH, CSP Certified Industrial Hygienist

JMG/JNS/SA

Attachments: Attachment A - Analytical Laboratory Report and Chain of Custody

Attachment B - Sample Locations Diagram



Attachment A

Analytical Laboratory Report and Chain of Custody



Report Date: September 11, 2014

Jonathan N. Schatz Tidewater, Inc. 6625 Selnick Drive Suite A Elkridge, MD 21075 Phone: 410-997-4458 Fax: 410-997-8713

E-mail: jonathan.schatz@tideh2o.net

Workorder: 34-1424123

Client Project ID: 082714-FOH 082814

Purchase Order: 082714-FOH Project Manager: Jessica Helland

Analytical Results

Sample ID: 082714-A01				Collected: 08/27/2014
Lab ID: 1424123001	Samp	Received: 08/28/2014		
Method: NIOSH 5605	Sampli		C 226-58, Sorbent Tube, D-2 OVS, Quartz Filter Volume 123 L	Analyzed: 09/10/2014
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	<0.0041	0.50	
Pyrethrum	<0.50	< 0.0041	0.50	

Sample ID: 082714-A02				Collected: 08/27/2014
Lab ID: 1424123002	Samp	Received: 08/28/2014		
Method: NIOSH 5605	Sampli	Media: SKC 226-58, Sorbent Tube, XAD-2 OVS, Quartz Filter npling Parameter: Air Volume 126 L		Analyzed: 09/10/2014
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	<0.0040	0.50	
Pyrethrum	<0.50	<0.0040	0.50	

Sample ID: 082714-A03				Collected: 08/27/2014
Lab ID: 1424123003	Samp	Received: 08/28/2014		
Method: NIOSH 5605	Sampli	Media: SK XA ng Parameter: Air	Analyzed: 09/10/2014	
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	< 0.0039	0.50	
Pyrethrum	<0.50	< 0.0039	0.50	

ADDRESS 960 West LeVoy Drive, Salt Lake City, Utah, 84123 USA | PHONE +1 801 266 7700 | FAX +1 801 268 9992 ALS GROUP USA, CORP. An ALS Limited Company



www.alsglobal.com

RIGHT SOLUTIONS RIGHT PARTNER



Workorder: **34-1424123**

Client Project ID: 082714-FOH 082814 Purchase Order: 082714-FOH Project Manager: Jessica Helland

Analytical Results

Sample ID: 082714-A04				Collected: 08/27/2014	
Lab ID: 1424123004	Samp	Sampling Location: 082714-FOH			
Method: NIOSH 5605	Sampli	Media: SKC 226-58, Sorbent Tube, XAD-2 OVS, Quartz Filter Sampling Parameter: Air Volume 129 L			
Analyte	ug/sample	mg/m³	RL (ug/sample)		
Piperonyl butoxide	<0.50	< 0.0039	0.50		
Pyrethrum	<0.50	< 0.0039	0.50		

Sample ID: 082714-A05				Collected: 08/27/2014
Lab ID: 1424123005	Samp	ling Location: 08	2714-FOH	Received: 08/28/2014
Method: NIOSH 5605	Sampli	THE PART OF THE PA	C 226-58, Sorbent Tube, D-2 OVS, Quartz Filter Volume 129 L	Analyzed: 09/10/2014
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	< 0.0039	0.50	
Pyrethrum	<0.50	< 0.0039	0.50	

Sample ID: 082714-A06 Lab ID: 1424123006				Collected: 08/27/2014 Received: 08/28/2014
Method: NIOSH 5605	Sampli	Media: SKC 226-58, Sorbent Tube, XAD-2 OVS, Quartz Filter Sampling Parameter: Air Volume 128 L		
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	< 0.0039	0.50	
Pyrethrum	<0.50	< 0.0039	0.50	

Sample ID: 082714-A07				Collected: 08/27/2014
Lab ID: 1424123007	Samp	Received: 08/28/2014		
Method: NIOSH 5605	Sampli	Media: SK XA ng Parameter: Air	Analyzed: 09/10/2014	
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	< 0.0037	0.50	
Pyrethrum	<0.50	< 0.0037	0.50	

Sample ID: 082714-A08 Lab ID: 1424123008	Samp	ling Location: 08	2714-FOH	Collected: 08/27/2014 Received: 08/28/2014
Method: NIOSH 5605	Samplii		C 226-58, Sorbent Tube, D-2 OVS, Quartz Filter Volume 135 L	Analyzed: 09/10/2014
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	< 0.0037	0.50	

Results Continued on Next Page



Workorder: 34-1424123

Client Project ID: 082714-FOH 082814 Purchase Order: 082714-FOH Project Manager: Jessica Helland

Analytical Results

Sample ID: 082714-A08				Collected: 08/27/2014
Lab ID: 1424123008	Samp	oling Location: 08	2714-FOH	Received: 08/28/2014
Method: NIOSH 5605	Sampli	THE RESIDENCE OF THE RESIDENCE OF THE PROPERTY	C 226-58, Sorbent Tube, D-2 OVS, Quartz Filter Volume 135 L	Analyzed: 09/10/2014
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Pyrethrum	<0.50	< 0.0037	0.50	Section (Charles to Section

Sample ID: 082714-A09				Collected: 08/27/2014
Lab ID: 1424123009	Samp	ling Location: 08	2714-FOH	Received: 08/28/2014
Method: NIOSH 5605	Sampli		C 226-58, Sorbent Tube, D-2 OVS, Quartz Filter Volume 137 L	Analyzed: 09/10/2014
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	< 0.0036	0.50	
Pyrethrum	<0.50	< 0.0036	0.50	THE PARTY OF THE P

Sample ID: 082714-A10				Collected: 08/27/2014
Lab ID: 1424123010	Sampl	Received: 08/28/2014		
Method: NIOSH 5605	Samplin	Media: SKC 226-58, Sorbent Tube, XAD-2 OVS, Quartz Filter Sampling Parameter: Air Volume Not Applicable		
Analyte	ug/sample	mg/m³	RL (ug/sample)	
Piperonyl butoxide	<0.50	NA	0.50	
Pyrethrum	<0.50	NA	0.50	1000 1000 1000 1000 1000 1000 1000 100

Sample ID: 082714-W01				Collected: 08/27/2014
Lab ID: 1424123011	Sampling Location: 082714-FOH			Received: 08/28/2014
Method: NIOSH 5605	Media: Wipe Sampling Parameter: Area Not Provided		Analyzed: 09/10/2014	
Analyte	ug/sample	RL (ug/sample)		
Piperonyl butoxide	<0.50	0.50		
Pyrethrum	<0.50	0.50		1. 为能性的是最高的特殊的基础的是是 对

Sample ID: 082714-W02			Collected: 08/27/2014
Lab ID: 1424123012	Sa	ampling Location: 082714-FOH	Received: 08/28/2014
Method: NIOSH 5605	San	Media: Wipe npling Parameter: Area Not Provided	Analyzed: 09/10/2014
Analyte	ug/sample	RL (ug/sample)	
Piperonyl butoxide	<0.50	0.50	
Pyrethrum	<0.50	0.50	



Workorder: **34-1424123**

Client Project ID: 082714-FOH 082814 Purchase Order: 082714-FOH Project Manager: Jessica Helland

Analytical Results

		Collected: 08/27/2014
Sa	ampling Location: 082714-FOH	Received: 08/28/2014
Media: Wipe Sampling Parameter: Area Not Provided		Analyzed: 09/10/2014 ed
ug/sample	RL (ug/sample)	
<0.50	0.50	
<0.50	0.50	
	San ug/sample <0.50	Sampling Parameter: Area Not Provide ug/sample RL (ug/sample) <0.50 0.50

Sample ID: 082714-W04			Collected: 08/27/2014
Lab ID: 1424123014			
Method: NIOSH 5605	Media: Wipe Sampling Parameter: Area Not Provided		Analyzed: 09/10/2014
Analyte	ug/sample	RL (ug/sample)	
Piperonyl butoxide	<0.50	0.50	
Pyrethrum	<0.50	0.50	

Sample ID: 082714-W05			Collected: 08/27/2014
Lab ID: 1424123015	Sa	ampling Location: 082714-FOH	Received: 08/28/2014
Method: NIOSH 5605	Media: Wipe Sampling Parameter: Area Not Provided		Analyzed: 09/10/2014
Analyte	ug/sample	RL (ug/sample)	
Piperonyl butoxide	<0.50	0.50	
Pyrethrum	<0.50	0.50	

Sample ID: 082714-W06				Collected: 08/27/2014
Lab ID: 1424123016	Sa	Sampling Location: 082714-FOH		Received: 08/28/2014
Method: NIOSH 5605	Media: Wipe Sampling Parameter: Area Not Provided		Analyzed: 09/10/2014	
Analyte	ug/sample	RL (ug/sample)		
Piperonyl butoxide	<0.50	0.50		
Pyrethrum	<0.50	0.50	Bell May 1970 e	

Sample ID: 082714-W07			Collected: 08/27/2014
Lab ID: 1424123017	Sa	ampling Location: 082714-FOH	Received: 08/28/2014
Method: NIOSH 5605	Media: Wipe Sampling Parameter: Area Not Provided		Analyzed: 09/10/2014
Analyte	ug/sample	RL (ug/sample)	
Piperonyl butoxide	<0.50	0.50	
Pyrethrum	<0.50	0.50	



Workorder: 34-1424123

Client Project ID: 082714-FOH 082814

Purchase Order: 082714-FOH Project Manager: Jessica Helland

Analytical Results

Sample ID: 082714-W08			Collected: 08/27/2014
Lab ID: 1424123018	Sa	ampling Location: 082714-FOH	Received: 08/28/2014
Method: NIOSH 5605	San	Media: Wipe npling Parameter: Area Not Provided	Analyzed: 09/10/2014
Analyte	ug/sample	RL (ug/sample)	
Piperonyl butoxide	<0.50	0.50	
Pyrethrum	<0.50	0.50	

Sample ID: 082714-W09			Collected: 08/27/2014
Lab ID: 1424123019	Sa	ampling Location: 082714-FOH	Received: 08/28/2014
Method: NIOSH 5605	San	Media: Wipe npling Parameter: Area Not Provided	Analyzed: 09/10/2014
Analyte	ug/sample	RL (ug/sample)	
Piperonyl butoxide	<0.50	0.50	
Pyrethrum	<0.50	0.50	

Sample ID: 082714-W10			Collected: 08/27/2014
Lab ID: 1424123020	Sa	Received: 08/28/2014	
Method: NIOSH 5605	San	Analyzed: 09/10/2014	
Analyte	ug/sample	RL (ug/sample)	
Piperonyl butoxide	<0.50	0.50	
Pyrethrum	<0.50	0.50	

Report Authorization (/S/ is an electronic signature that complies with 21 CFR Part 11)

Method	Analyst	Peer Review
NIOSH 5605	/S/ Pooreun Lim	/S/ Thomas J. Masoian
	09/11/2014 11:09	09/11/2014 12:09

Laboratory Contact Information

ALS Environmental 960 W Levoy Drive Salt Lake City, Utah 84123 Phone: (801) 266-7700

Email: alslt.lab@ALSGlobal.com

Web: www.alsslc.com



Workorder: 34-1424123

Client Project ID: 082714-FOH 082814

Purchase Order: 082714-FOH Project Manager: Jessica Helland

General Lab Comments

The results provided in this report relate only to the items tested.

Samples were received in acceptable condition unless otherwise noted.

Samples have not been blank corrected unless otherwise noted.

This test report shall not be reproduced, except in full, without written approval of ALS.

ALS provides professional analytical services for all samples submitted. ALS is not in a position to interpret the data and assumes no responsibility for the quality of the samples submitted.

All quality control samples processed with the samples in this report yielded acceptable results unless otherwise noted.

ALS is accredited for specific fields of testing (scopes) in the following testing sectors. The quality system implemented at ALS conforms to accreditation requirements and is applied to all analytical testing performed by ALS. The following table lists testing sector, accreditation body, accreditation number and website. Please contact these accrediting bodies or your ALS project manager for the current scope of accreditation that applies to your analytical testing.

Testing Sector	Accreditation Body (Standard)	Certificate Number	Website
Environmental	ACLASS (DoD ELAP)	ADE-1420	http://www.aclasscorp.com
	Utah (NELAC)	DATA1	http://health.utah.gov/lab/labimp/
	Nevada	UT00009	http://ndep.nv.gov/bsdw/labservice.htm
	Oklahoma	UT00009	http://www.deq.state.ok.us/CSDnew/
	Iowa	IA# 376	http://www.iowadnr.gov/InsideDNR/RegulatoryWater.aspx
	Florida (TNI)	E871067	http://www.dep.state.fl.us/labs/bars/sas/qa/
	Texas (TNI)	T104704456-11-1	http://www.tceq.texas.gov/field/qa/lab_accred_certif.html
Industrial Hygiene	AIHA (ISO 17025 & AIHA IHLAP/ELLAP)	101574	http://www.aihaaccreditedlabs.org
Lead Testing:			
CPSC	ACLASS (ISO 17025, CPSC)	ADE-1420	http://www.aclasscorp.com
Soil, Dust, Paint ,Air	AIHA (ISO 17025, AIHA ELLAP and NLLAP)	101574	http://www.aihaaccreditedlabs.org
Dietary Supplements	ACLASS (ISO 17025)	ADE-1420	http://www.aclasscorp.com

Definitions

LOD = Limit of Detection = MDL = Method Detection Limit, A statistical estimate of method/media/instrument sensitivity.

LOQ = Limit of Quantitation = RL = Reporting Limit, A verified value of method/media/instrument sensitivity.

ND = Not Detected. Testing result not detected above the LOD or LOQ.

NA = Not Applicable.

< This testing result is less than the numerical value.

^{**} No result could be reported, see sample comments for details.

⁽⁾ This testing result is between the LOD and LOQ and has higher analytical uncertainty than values at or above the LOQ.



ALS Environmental
Field Chain-of-Custody Record

52/h2h/

10 10 10 10 10 10 10 10	Client Name & Address: Thurs Le. INC.	·i.	Project No.:		4	ро			Analys	Analyses Requested	ted	1	
1/2 1/2	AS SEINICK DOING, SHE F		80	1		O noi						s.	
10 - 5 1 - 6 1 10 - 10 10 10 10 10 10	Midze, MD Aloty		Project Name:			levie:		H () () () ()	ixotx			nenist	io.
12 12 12 12 12 12 12 12	1		0	87714-12	<i>H</i> ₀	Pres			· [1			uoŋ ,	1) Cool to 4°C 2) HCl to pH<2, 4°C
127 min 127			Sampler: (Sign:	ature)					hNO			lo. ol	3) H ₂ SO ₄ to pH<2, 4°C 4) HNO ₃ to pH<2, 4°C
12 min 1	nall: Moun - Jun Min @ + Mebho	int	1		7			4071	so d			4	 NaOH to pH>12, 4°C ZnOAcNaOH to pH>9, 4°C
7.73 126 min	eld Sample Number Site ID	Date	Time	Ve/W/AC	ALS Sample Number			y	:0				Remarks
128 min 128 L		41/64/8	12 min	Title			π	メ	×				1
129 m² 1	8m	. <u> </u>	126 MIN	777					×				
129 min 129 L	RA		148 mir	7841				~	~				
1	1 S.M	,	129 mir	1491				~	×				
13 14 15 15 15 15 15 15 15			1 ×9 min	7 671			-	×	X				1
13 y mu 13 y L			1,48 min	7841				×	×				
137 min 13# L			134 ms	1346				×	×		3		
A y g y C	804		175 mm	1356				×	×				
Achive for Months Sample Disposal Sample Disposal Skin Intiant Client Skin Intiant Client Client Chick of Chick for Months Client Client Chick of Chick Client Chick	bod		139 Mix	7起1			- 2	×	×				
Archive for Months Client Archive for Months Client Archive for Months Client C	-	×	t///	11/19			<u> </u>	ĸ.	K				
Poison Unknown Disposal by Lab (Rush = email data by CoB on day due. Surcharges assessed if samples are retained longer than 3 months) Carrier/Airbill #: A Date Time Shipped to: Received by: (Signature) Carrier/Airbill #: Date Time Shipped to:	sible Hazard Identification	□ Rad	Sample Dispor	sal		_	rchive fo			equested 2	Turn Arou (Rush)	Ind Time	Rush)
Received by: (Signature) Date Time			Disposal b	y Lab	are retained longer tha	an 3 mont	(Sr		□ ਲ	3 Days	(Rush) data by Çel	Day due.	Surcharges assessed.)
Received by: (Signature) Received by: (Signature) Received by: (Signature) Received by: (Signature) Date Time							-	Carrier/A	irbill #:		Ü	1 Day	TAT
Received by: (Signature) Received by: (Signature) Received by: (Signature) Date Time	nquished by: (Signature)			Received by: (Si	gnature)					Date	1/	Shipped to	
Received by: (Signature) Received by: (Signature) Date Time	1								(3)	41/848	1022	ALS Enviro	nmental
Received by: (S/gnature) Date Time	naysthed by:48tgnature)			Received by: (Si	gnature)				5	Date	Time	960 West L Salt Lake C Phone: (80	eVoy Drive ity, UT 84123 0) 356-9135
	inquished by: (Signature)			Received by: (Si	gnature)					Date	Time	Phone: (80 FAX: (80	1) 266-7700 1) 268-9992

13386/12

ALS Environmental

Field Chain-of-Custody Record

6

Page /

M. Mi. 21 Days 21 Day 5) NaOH to pH>12, 4°C 6) ZnOAcNaOH to pH>9, 4°C (Rush = email data by COB on day-due. Surcharges assessed.) B) Bulk F) Filter G) Wipe M) Media 3) H2SO4 to pH<2, 4°C 4) HNO, to pH-2, 4°C Preservation Codes: NISH GULY Remarks 2) HCI to pH<2, 4°C Salt Lake City, UT 84123 YON TAI Phone: (800) 356-9135 Phone: (801) 266-7700 FAX: (801) 268-9992 1) Cool to 4°C Matrix Codes: 960 West LeVoy Drive L) Liquid S) Sail C) Solid W) Water Requested Turn Around Time

2 Days (Rush) The 7 Days (Rush)

3 Days (Rush) 14 Days 022 ALS Environmental Shipped to: No. of Containers Time Time Analyses Requested 190/00 Date Date Carrier/Airbill #: Months 1 X. Y X X × × X ☐ Archive for _ Sample for Matrix QC 10 Sample Matrix Code (fees may be assessed if samples are retained longer than 3 months) zl 17. Preservation Code ALS Sample Number My Challeton Received by: (Signature) Received by: (Signature) Received/by: (Signature) 431 -4KK80 NBY-WITTED 270 D Disposal by Lab ☐ Return to Client Sampler: (Signature) Sample Disposal Project Name: Shh! 1436 1475 4541 1475 3441 1933 1936 1441 WEY/8 Unknown Date tidakoinet Client Name & Address: Tulian Un, INL. 6685 Selmin Move, Suit 19 5/48 28 45 WV 5400 5252 Skin Irritant 3255 Field Black 146 PN 5720 2484 572 8409-195-114 Poison Possible Hazard Identification ELHALL IN NOTE - to6 1/2 27 Pin 84 7 12 M 77 3 Relinquished by: (Signature) Relinquished by: (Signature) Relinquished by: (Signature TASENO JAN MAN ESM - HITES 1 W. 2 103M-40M - HEYSO - Wer 80M - HILY80 DOM - HIEYSO 01M- 4/2883 Field Sample Number ZOM - MEXXO WO Non-Hazard Flammable -41£883 MERSO W12480 4/tx82 Phone: e-mail: FAX: 口匠 d .

White - Laboratory Copy

Yellow - Client Copy

5/11/2011

Schultz Company P. O. Box 4408 Bridgeton, MO 63044-0406

Material Safety Data Sheet Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

Hazardous Material Identification System - (HMIS) HEALTH - 1 REACTIVITY - 0 PERSONAL -FLAMMABILITY - 0 Rubber gloves

Product Type: Liquid ready-to-use in	secticide		
Product Item Number: HG-10422X-5		Formula Code Number: 21-0522	
EPA Registration Number Manufacturer			Emergency Telephone Numbers
Chemsico Division of United In 8494 Chapin Industri St. Louis, MO 63114		al Drive	For Chemical Emergency: 1-800-633-2873 For Information: 1-800-257-3379 Prepared by: C. A. Duckworth Date Prepared: October 5, 2007
II Hazards Ingredient/Identity Informat	ion	III Physical and Chemical Characteristics	
Chemical % OSHA PEL ACGIH TLV Pyrethrins 0.02 NA 5 mg/m³ CAS# 8003-34-7 Piperonyl buloxide 0.20 NA NA CAS# 51-03-6 NA NA NA		Appearance & Odor: Bolling Point: Mailing Point: Vapor Pressure: Specific Gravily: Vapor Densily: % Votalile (by vol.): Solubility in Water: Evaporallon Rate:	Sproy mist with clear wet film. 215° F NA NA 1.0 (H ₂ O = 1) Greater than 1 (Air = 1) 99% Greater than 99% Less than 1 (Bulyl Acetate = 1)
IV Fire and Explosive Hazards Data		V Reactivity Data	
Decomposition Temperature: NA Special Fire-Fighting Procedures: Use procedures original fire	on dioxide, Dry chemical	Stability: Stable Polymerization: Will not occur Conditions to Avold: None Incompatible Materials: NA Hazardous Decomposition or Byproducts: NA	
VI Health Hazard Data		VII Precautions fo	r Safe Handling and Use
Ingestion (Swallowing); Harmful if swallowed. First control center or doctor immediately for treatments in a glass of water if able to swallow. Do not indicted to so by a Poison Control Center or doctor. Not mouth to an unconsclaus person. Skin Contact: through skin. First Ald: Take off contaminated alc immediately with plenty of water for 15-20 minute. Center or doctor for froatment advice. Eye Conteyes. First Ald: Hold eye open and rinse slowly an 15-20 minutes. Remove contact lenses if present then continue rinsing eye. Inhalation Toxicily: If in fresh oir. If person is not breathing call 911 or an adrificial respiration, preferably mouth-to-mouth. Avoid breathing vapors.	ant advice. Have person luce vontiling unless told ever givo anything by Hamful if obsorbed othing. Rinse skin es. Call a Poison Control act: Avoid contact with ad gently with water for after the first five minutes haled move person to	Avoid contact with fi Waste Disposal: Do not reuse contain If particity filled: Call you instructions. Handling & Storage Pre	ase Material is Released or Spilled: quid. Soak up with obsorbent material. ner. Place in trash or offer for recycling if avoilabla. pur local solid waste agency for disposal cautions: emperatures can exceed 54° C/130° F.
Special Notes: None Health conditions Aggravated by Exposure: None undor normal use ingredients listed by NTP, OSHA, or IARC as Carcinogens or Potential Carcinogens: None			
VIII Control Measures		IX Transportation Data	
Read and follow label directions. They ore your best guide to using this product effectively, and give necessary safety precautions to protect your health.		IMDG: Not Regulated b	DOT (limited quantity exception) by IMDG (limited quantity exception) y IATA (limited quantity exception)

The information and statements herein are believed to be reliable but are not to be construed as warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.



Attachment B Sample Locations Diagram

